

## Product information:

**General properties:** Beton Betone Super Release Agent was developed as a clear parting agent between stamp tools and fresh concrete or polymer modified micro-topping & overlay mix products including Beton Betone micro-topping & overlay mix. Beton Betone Super Release Agent should be sprayed over fresh concrete, grout or micro-topping & overlay mix as well as to the texturing stamp creating a bond breaking barrier which prevents the texturing tools from sticking or material pulling off. In addition, Beton Betone Liquid Release prolongs tool life by decreasing friction between the stamping mats and the concrete or micro-topping & overlay mix. It is recommended to clean the treated substrate with a neutral detergent for micro-topping & overlay mix or Beton Betone Profiler Green Clean for concrete before the application of Beton Betone Color Floor, Color Wall or Color Accents.

- Clear release agent
- Minimal to no residue
- Bubblegum scent
- Interior or exterior applications
- Able to re-stamp after initial lift

**Recommended use:** Release agent for fresh concrete and polymer modified micro-topping & overlay mix systems including Beton Betone micro-topping & overlay mix.

**Not recommended for:** Cured or hardened concrete and micro-topping & overlay mix systems

**Colors:** Clear liquid

**Coverage per gallon:**

Concrete	700 square feet
micro-topping & overlay mix	600 Square feet

**Packaging:** 5 Litters

**Storage conditions:** Cool and dry environment.

**Shelf life:** 12 months

**Ordering information:**

Prices may be obtained from Regional Sales Representative or local Beton Betone Decorative Concrete Products Outlet.

Upon information, belief and to the best of our knowledge, the information contained herein is true and accurate as of the date of issuance of this particular product and any and all information conveyed, expressed or implied is subject to change without prior notice. We guarantee our products to conform to Beton Betone Products' quality control mechanisms, but not to any other standards. We assume no responsibility for coverage, performance or injuries resulting from use, misuse or uses not described in any promotional materials. Promotional materials are not a supplementation to any contract or expand any term or condition of the product purchase agreement, if any is reduced to writing. Liability, if any, is limited to replacement of the purchased product upon presentation of valid sales receipt or invoice, and no damages for any consequential, liquidated or other damages are provided under this Limitation of Liability and Limited Warranty. NO OTHER WARRANTY OR GUARANTY OF ANY KIND IS MADE BY BETON BETONE PRODUCTS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. DO NOT PURCHASE AND USE THIS PRODUCT IF YOU HAVE NOT AGREED TO THE ABOVE TERMS.

beton betone is a trade name, anywhere in this document is written beton betone the intention is also to nichsey haez shivock vyizom nadlan ltd

## Application Instructions:

These instructions are not intended to show product recommendations for specific service. They are issued as an aid in determining correct application procedure. These instructions should be followed closely to obtain the maximum service from the product.

**Area Preparation:** Be sure to mask or cover all areas that are not intended to be treated with liquid release.

### Application:

- 1) Allow the concrete /micro-topping & overlay mix to adequately set for texturing with stamp tools. Beton Betone micro-topping & overlay mix does not require set time,
- 2) Utilizing a traditional pump-up sprayer, mist Beton Betone Super Release to the stamping tool as well as to an area that will be stamped within a 10 minute time period. Super Release may be re-applied to the intended stamp area if release agent evaporates.
- 3) Repeat Step 2 until installation is complete. Re-apply liquid release to stamp tool if material pull off is experienced

### Removal/Surface Preparation:

- 1) Allow concrete/micro-topping & overlay mix to adequately cure, allowing the applicator(s) to walk on the application area without scarring.
- 2) Clean textured micro-topping & overlay mix with a neutral detergent and agitation. Utilize Beton Betone Profiler Green Clean for preparation of textured concrete.
- 3) For exterior application, utilizing a 12,000 work units\* pressure washer in conjunction with a 0 degree rotating tip, remove the Profiler Green Clean /neutral detergent with overlapping line patterns. For interior surface preparation, agitate Beton Betone Profiler Green Clean /neutral detergent utilizing a floor buffer (small area) or an auto-scrubber (large area) with a brush attachment while rinsing with clean water. Extract material utilizing a wet/dry vacuum or lower the squeegee uptake bar on the auto-scrubber. Continue to flush and agitate the substrate until the rinse water is clear. Be careful not to scar the textured substrate or allow the Profiler Green Clean /neutral detergent to dry on the surface.

### Stain/Seal:

Allow the intended application area to thoroughly cure (concrete 28 days) before the application of Beton Betone stains and/or sealers.